



KONGERIKET NORGE

The Kingdom of Norway

09/555592 PCT/NO 98/00336

REC'D 07 DEC 1998

WIPO

PCT

Bekreftelse på patentsøknad nr
Certification of patent application no

19975518

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

► Det bekreftes herved at vedheftede dokument er nøyaktig utskrift/kopi av ovennevnte søknad, som opprinnelig inngitt 1997.12.01

► It is hereby certified that the annexed document is a true copy of the above-mentioned application, as originally filed on 1997.12.01

1998.11.16

Freddy Strømmen

Freddy Strømmen
Seksjonsleder

Mette E. Hansen

Mette E. Hansen



PATENTSTYRET

Styret for det industrielle rettsvern

1c

PATENTSTYRETT
01.DES97 975518

1. desember 1997
5 JGS/kr
O:125123
ETOP97028

10 SØKER:
Telefonaktiebolaget LM ERICSSON
S-126 25 Stockholm
Sverige

15

20

OPPFINNERE:
Øyvind Breivik
Drammensveien 50c
25 0271 Oslo
Paul Torkil Fjuk
Hellaveien 79
2013 Skjetten

30

TITTEL:
Fremgangsmåte for forbedring av oppsettingen av
telefon-til-telefon-anrop
35

FULLMEKTIG:
Oslo Patentkontor AS, Postboks 7007M, 0306 Oslo

METHOD FOR IMPROVING THE SETUP OF TELEPHONE-TO-TELEPHONE CALLS

5 Field of the invention

Generally, the present invention relates to Internet telephony and intelligent networks (IN) function.

More specifically, the present invention relates to a
10 method for improving the setup of telephone-to-telephone calls using telephones connected to a PSTN/ISDN access network and using a separat network, especially Internet as a substantial by-pass network, special telephone gateways (GW) forming bridges between the access network
15 and said by-pass network, and connections being established between the user telephones (A,B) and the gateways (GW) that bridge the call.

20 Background of the invention

The application area of the present invention has been developed in connection with low tariff international telephone-to-telephone calls using the Internet as the main
25 carrier network, but the general aspect of the invention may also be related to any quality of service required.

Furthermore, the present invention is applicable not oly
to international and long distance services but also to
30 any other geographically segmented services (e.g. local, regional, national).

Users have telephones connected to the PSTN/ISDN network. The Internet can be used to carry portions of the traditional PSTN/ISDN telephone-to-telephone calls. Special
35 Internet telephony gateways GW form bridges between the PSTN/ISDN access network and the Internet (which acts as the carrier network).

In a traditional telephone-to-telephone call, a connection between two parties is established at the call set-up phase. The originating party and the terminating party are identified by their respective telephone numbers (caller A-num and callee B-num) during the set-up phase. Call logic is handled by the PSTN/ISDN network.

In a telephone-to-telephone call using the PSTN/ISDN network as the access network and the Internet as the main carrier network, connections must be established between the user telephones and the gateways that bridge the call. The present invention presents a solution to the handling of call-establishment to the originating gateway. Extensions and enhancements to the basic invention are described later.

Prior art

Existing solution and problems with these

Referring to Figure 1, there will now be given a description about how a traditional international call path is established.

The known solutions handle call establishment in two phases. First, the caller (A) is required to set up a connection to a preferred originating gateway (Gwa). Second, the caller is required to dial the desired number that identifies the terminating telephone (B-num).

As an illustration, a typical, although simplified, call handling sequence is as follows:

1. The caller (A) obtains a PSTN/ISDN connection to an originating gateway (Gwa) by dialing the gateway number.
2. Gwa sends a new dial tone or a voice message to A to indicate that the connection has been established.

3. The caller (A) dials the number that identifies the callee (B). (The gateway may extract the B-number from the connection by interpreting Dual Tone Multiple Frequency (DTMF) signals. Prior to this A may need to enter a PIN number or similar for authorization purposes).
 4. Gwa performs a number analysis on the B-number to find the closest GW (Gwb) to B.
 5. Gwa establishes a data connection (connection oriented or connectionless) to the terminating gateway (Gwb) and transfers the B-number to Gwb using the data network.
 6. Gwb in turn establishes the final PSTN/ISDN connection to the called party (B).
- One advantage of the known solutions, in this context, is that they make use of standard PSTN/ISDN functions. However, the known solutions require the caller to handle the call set up in two distinct phases which is cumbersome. The caller is also required to know the telephone number of the preferred (i.e., closest) gateway. Indeed, the caller may need to keep a list of gateway telephone numbers if the preferred one is busy, or if it is down, or if other circumstances make it unavailable.
- There are also other problems to the known solutions. These are addressed in a later chapter which provides extensions to the present invention described prior thereto.

Objects of the present invention

An object of the present invention is to provide a method for improving the setup of telephone-to-telephone calls in relation to the prior art procedures.

Another object of the present invention is to provide a method by which the caller is allowed to handle the call set-up in one single phase, as in the case of traditional "local" telephone calls.

- 5 More specifically, an object of the present invention is to make the associated gateways transparent to the caller.

Still another object of the present invention is to utilize Internet telephony and intelligent networks (IN)
10 functions in a far more efficient and less costly manner.

Brief disclosure of the invention

The above objects are achieved in a method as stated in the preamble, which according to the present invention is
15 characterized in that for the purpose of making the gateways transparent to the caller (A) the method allows the caller (A) to dial a by-pass network service prefix together with the number of the callee (B).

- 20 More specifically, it is according to the invention suggested that said by-pass network service prefix, i.e. an IN service prefix is adapted to identify the relevant IN service for thereby routing the call to an IN node which can execute this IN service.

25 In other words, the present invention allows the caller to handle the call set-up in one single phase, just as in case of conventional telephone calls, at the same time as the gateways appear transparent to said caller.

30 Further features and advantages of the present invention will appear from the following description taken in conjunction with the enclosed drawings, as well as from the appending patent claims.

35

Brief disclosure of the drawings

Fig. 1 is a sketch illustrating a traditional international call path.

5

Fig. 2 is a sketch illustrating an embodiment of the method according to the present invention.

10 Detailed description of embodiments

Fig. 1 illustrates a traditional international call path, which has been discussed previously, and wherein the set-up of telephone-to-telephone calls are made using
15 telephones connected to a PSTN/ISDN access network and using a separate network, here the Internet as a substantial by-pass network, special telephone gateways GWa and GWb forming bridges between the access network and said
20 by-pass network, and connections being established between a caller telephone A and a callee telephone B through appropriate gateways GWa and GWb.

An embodiment of the present method is illustrated in Fig. 2, wherein the handling of call establishment will
25 only take place in one phase.

More specifically, the present solution uses the Intelligent Network to:

- 30 1. Allow the user to establish a call in one single phase.

The user dials one number: IN service prefix + B-number. IN service prefix identifies the IN service:

- 35 'International calls over the Internet'. IN service prefix is used to route the call to the IN node which executes this IN service.

2. Automatically find the closest/available gateway

The IN service will establish the call to GW, hereby named Gwa. In the call setup the Gwa number is included as destination number. In addition, the A and B-number is included.

CallingPartyNumber: A-number
CalledPartyNumber: Gwa-number
RedirectingNumber: B-number

a = A dials: (IN service prefix + B-number) in one sequence

20 CallingPartyNumber: A-number
 CalledPartyNumber: (IN service prefix +
 B-number)

25 CallingPartyNumber: A-number
 CalledPartyNumber: Gwa-number
 RedirectingNumber: B-number

1. The invention couples gateway functionality with IN
30 which makes the gateway equipment dependent on IN
functionality. The provider of such a service becomes
dependent on an operator with the specific IN
functionality.

2. Still address analysis in Gwa (see Extensions).

Advantages

- Call establishment in one step only.
- 5 • Since IN service logic is coupled to the GW application, value added functionality can easily be included (such as automatically finding the closest or available gateway).
- Number analysis can now be coupled with other services such as short numbers for a virtual network, and UPT.

10

Extensions and enhancements to the present invention

The problem area: Gwa still needs to analyse the B-number to find the GW closest to user B. Having these number analysis functions distributed implies that many Gws must
15 be updated when changes in the network occur. This is a network management problem which the extension to the basic invention solves.

Existing solutions and problems with these: The Gws can perform complete number analysis functions with B-number as input and Gwb address as result. This analysis must
20 then be in every GW and the network will be hard to maintain.

The invention: An extension to the basic invention can be made to solve the problem in such a way as to find the
25 closest terminating gateway for any terminating B-number.

IN can be used to locate the terminating gateway. Suppose that A calls a B-number. In addition to finding the E.164 number to Gwa, IN can also find the IP-address to Gwb
30 which is the gateway closest to the user B.

1. The IN maintains a list of the gateways, with their respective IP-address and the respective area code(s).
2. Based on the area code of the B-number the IP-address to the closest GW is found.
- 5 3. In the call setup towards Gwa the IP-address of Gwb is included.
4. Gwa uses the received Gwb IP-address in the remaining call handling process.

A proposal/example on how this can be transferred on ISUP
 10 (IAM message)/DSS1 (SETUP message):

CallingPartyNumber: A-number
 CalledPartyNumber: Gwa-number
 RedirectingNumber: B-number
 Subaddress: Gwb IP-address

15 The information flow (see Figure 2) is as follows:

a = A dials: (IN service prefix + B-number)
 in one sequence

b = Call routed to IN:

20 CallingPartyNumber: A-number
 CalledPartyNumber: (IN service prefix +
 B-number)

c = Call routed to Gwa:

25 CallingPartyNumber: A-number
 CalledPartyNumber: Gwa-number
 RedirectingNumber: B-number
 Subaddress: Gwb IP-address

Broadening

30 The application has only addressed the Internet as the carrier or bypass network but the application can be broadened to, in general, address networks based on IP-technology and even to other packet based networks or

technology, such as Frame Relay, ATM, hybrids of these, and so on.

Furthermore, the present invention is applicable not only to international and long distance services but also to
 5 any other geographically segmented services (e.g. local, regional, national).

References

10 WO-SE00680: "Speech connection set-up method for interconnected networks registering network address of users who has a telephone and PC on network, with telephone system and uses address when making call connection".

15 **Comments:** The WO-SE00680 patent is related to this patent application in the sense that it too uses certain IN functions to solve certain addressing problems related to the domain of gateways. Note, however, that it addresses a different problem within this domain. The following is
 20 a list to illustrate some of the differences:


- WO-SE00680 addresses an application area that have users connected to special PCs (PC connected telephones) - not plain old PSTN/ISDN telephones.

- WO-SE00680 uses IN primarily to locate called users
 25 using special PCs on a data network - not handle call set-up of telephone-to-telephone calls over the internet in one single phase.

- WO-SE00680 uses a register function to keep track of the location of the users and the gateway that the respective
 30 users have registered with - this patent application does not use such an explicit register function.

- WO-SE00680 transfers the IP-address of a called user to the gateway that the user has a priori registered with -

In its basic form this application only transfers the B-number of the called user. In its extended form the B-number and the IP-address of the terminating gateway is transferred to the originating gateway for the purpose of
5 addressing locating the nearest gateway.



ETOP97028

P a t e n t c l a i m s

- 5 1. Method for improving the setup of telephone-to-
telephone calls using telephones connected to a PSTN/ISDN
access network and using a separat network, especially
Internet as a substantial by-pass network, special tele-
10 phone gateways (GW) forming bridges between the access
network and said by-pass network, and connections being
established between the user telephones (A,B) and the ga-
teways (GW) that bridge the call,
c h a r a c t e r i z e d i n that for the purpose of
making the gateways transparent to the caller (A) the
15 method allows the caller (A) to dial a by-pass network
service prefix together with the number of the callee
(B).
2. Method as claimed in claim 1,
20 c h a r a c t e r i z e d i n that said by-pass
network service prefix, i.e. an IN service prefix is
adapted to identify the relevant IN service for thereby
routing the call to an IN node which can execute this IN
service.
- 25 3. Method as claim in claim 1 or 2,
c h a r a c t e r i z e d i n that said IN service is
arranged to find the most appropriate, e.g. the closest
gateway (GW) by analyzing the caller's number (A), and/or
30 possibly route the call to an alternative gateway if the
closest is busy, etc.
4. Method as claimed in any of the preceding claims,
c h a r a c t e r i z e d i n that after the IN ser-
35 vice has established the call (A) to the most appropriate
gateway (GW), (GWa) there is in the call setup included
the associated gateway number (GWa) as destination num-

ber, as well as the caller number (A) and the callee number (B).


- 5 5. Method as claimed in any of the preceding claims, characterized in that the IN service establishes the call (A) to the most appropriate gateway (Gwa) by coupling gateway functionality with an intelligent network (IN).
- 10 6. Method as claimed in any of the preceding claims, characterized in that address analysis is carried out in the gateway (Gwa) to which the call has been routed.
- 15 7. Method as claimed in any of the preceding claims, characterized in that value added functionality is included by service logic means of the intelligent network (IN), for example the automatic selection of the most appropriate and/or available gateway.
- 20 8. Method as claimed in any of the preceding claims, characterized in that number analysis is coupled with other services, for example short numbers for virtual network, and UPT.
- 25 9. Method as claimed in any of the preceding claims, characterized in that the most appropriate gateway for any terminating callee number (B) is carried out in the intelligent network (IN), i.e. by finding
- 30 the E.164 number to an appropriate gateway (Gwa), as well as the IP (Internet Protocol) address to the gateway (Gwb) closest to the callee (B).
- 35 10. Method as claimed in any of the preceding claims, characterized in that there is maintained an updated list of gateways in the by-pass network, i.e. the intelligent network (IN), as well as a list of respective IP-addresses and the respective area code(s).

11. Method as claimed in any of the preceding claims,
c h a r a c t e r i z e d i n that the area code of
the number (B) of the callee is used to find the IP-
5 address of the most appropriate callee gateway (GWb), for
example the closest gateway thereof.

12. Method as claimed in any of the preceding claims,
c h a r a c t e r i z e d i n that in the call setup
10 from the intelligent network (IN) towards the access
gateway (Gwa) the IP-address of the terminal gateway
(GWb) is included, so that the access gateway (Gwa) can
use the received terminal gateway (GWb) IP-address in the
remaining call handling process.

13. Method as claimed in any of the preceding claims,
c h a r a c t e r i z e d i n that the method allows
any caller (A) to dial a called part (B) via an access
network by only dialling once, i.e. a destination number.

14. Method as claimed in any of the preceding claims,
c h a r a c t e r i z e d i n that the most appropri-
ate gateway (Gwa) or gateways (Gwa, GWb) is/are selected
according to the quality of service (QoS) required, or
25 possibly according to other criteria, for example tariff,
availability, etc.



1/1

FIG.1




FIG.2

